

## JALAS® 9512 EXALTER

EN ISO 20347:2012, 01 SRC HRO

### PROPERTIES

Excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption, light

### SPECIFICATION

TYPE OF SHOE Occupational footwear, low shoes

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Exalter2

PLATFORM Performance

UPPER MATERIAL Microfiber, textile

UPPER MATERIAL THICKNESS 1,5-1,7

LINING MATERIAL Hygienical polyamide

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX3 Exalter2

INSOLE MATERIAL Textile, soft EVA, rigid EVA, polyester-based conductive thread, neo foam, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, grey, blue



**EXALTER<sup>2</sup>**



SIZE	ART. NO.	EAN NO.
36	9512-36	6408487444661
37	9512-37	6408487444678
38	9512-38	6408487444685
39	9512-39	6408487444692
40	9512-40	6408487444708
41	9512-41	6408487444715
42	9512-42	6408487444722
43	9512-43	6408487444739
44	9512-44	6408487444746
45	9512-45	6408487444753
46	9512-46	6408487444760
47	9512-47	6408487444777

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## JALAS® 9512 EXALTER

### FEATURES

Low weight, heat-resistant outsole, oil-resistant outsole, anti-static properties, ventilating insole, stabilizer, ergonomically shaped, double shock absorption zones, conforms with IEC 61340-5-1 (ESD), antibacterial fibre - counteracts odours, good environmental choice

### PRIMARY PROTECTION

Prevents risk of: sprain injuries, antistatic

### PRIMARY ENVIRONMENTS OF USE

Indoors, dry environments, clean environments



CE



Heat-resistant outsole



Oil-resistant outsole



Ergo-Shock Absorption System



Stabilizer



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-05-29

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 9512 EXALTER

**COMPLIANCE**  
EN ISO 20347:2012

### COMPLIANCE DESCRIPTION

O1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + A + E

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Heat-resistant outsole



Oil-resistant outsole



Ergothon Shock Absorption System



Stabilizer



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-05-29

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com